

Printed February 2, 2010

This Manual applies to Release 1
Modification 0 or later of Spool PDF Overlay/400™

Copyright 2009, 2010 **Broderick Data Systems**

This software is licensed material and cannot be used by anyone
who has not been authorized by **Broderick Data Systems**.

For additional information about this product please write to:

Broderick Data Systems
64 East Main Street
Lexington, Ohio 44904 USA
419-884-1844 EST
419-884-6112 (FAX)

sales@BroderickData.com
tech@BroderickData.com
<http://www.BroderickData.com>

TABLE OF CONTENTS

Chapter 1 Introduction

Commands	1-1
Cross Product Support	1-2

Chapter 2 Installation

Prerequisites.....	2-1
Installation	2-1

Chapter 3 Main Menu

Administration	3-1
Operation	3-2

Chapter 4 Define Tailoring Options

System Statistics	4-1
Passwords.....	4-1
Other Options.....	4-1
Access the BDS Software Server.....	4-3

Chapter 5 Define Options Specifications

Chapter 6 Define Font Global ID (FGID) Specifications

Chapter 7 Define FGID Substitution Table

Chapter 8 Spool Entry to PDF (SPLETOPDF) Command

Appendix A Electronic Media Distribution

Appendix B Retrieve Font Attributes Utility

Appendix C Acknowledgements

INTRODUCTION

Spool PDF Overlay/400™ is a product that will create IFS files in PDF format from spool entries. Spool entries containing images, multiple fonts, and Overlays (containing images and multiple fonts) are supported.

The following image compression techniques are supported:

- JPEG
- CCITT
 - G3 1D fax
 - G3 2D fax
 - G4 2D fax

*SCS and *AFPDS data streams are supported.

Optional Font Substitution is supported. Thus if the font resource is not found a similar one can be substituted.

Commands

The SPLETOPDF command can be executed from the command line or placed into CL programs. It creates an IFS file in PDF format from the specified spool entry.

Cross Product Support

Spool PDF Overlay/400 can be utilized by other products from Broderick Data Systems. The other product, if specified, will use Spool PDF Overlay/400 routines instead of product routines to create the PDF, then process the PDF as if its product routines created the PDF. The following products fully support using Spool PDF Overlay/400 to create PDF files:

SpoolOrganizer/400™: The Spool Organizer product can use Spool PDF Overlay/400 to create PDF files in all of its PDF-creating functions:

- Monitors
- Bundles
- Email
- Display/Print
- Optical

E-mail Utilities™: E-mail Utilities product can use Spool PDF Overlay/400 to create PDF files in all of its PDF-creating functions:

- Email a Spool Entry
- Write a Spool Entry to an IFS file

INSTALLATION

Prerequisites

The following hardware and system software is needed to execute Spool PDF Overlay/400. Please ensure that all needed system software is installed before beginning the installation.

AS/400:

- + OS/400 Version 5, Release 4, Modification 0 or greater
- + Security level 40 or less

Retrieve Font Attributes Utility:

To retrieve Font Attributes in existing PDF files:

- + Windows 2000, Windows XP, Windows 7, or Windows Server 2003
- + DotNet Framework 2.0 or greater

Installation

- 1) Sign on as **QSECOFR**

WARNING:

The instructions below are for loading Spool PDF Overlay/400 onto your system for the first time. If you are updating your existing Spool PDF Overlay/400 software to a new release, refer to the document “**Spool PDF Overlay/400 Update Instructions**”.

- 2) Restore the install routines from the media.

Mount the media and enter one of the following:

If you are using Tape:

```
RSTOBJ OBJ(BOVIN*) SAVLIB(SPDF40) DEV(xxxxxx) VOL(*MOUNTED)
RSTLIB(QTEMP)
```

If you are using CD-ROM:

```
RSTOBJ OBJ(BOVIN*) SAVLIB(SPDF40) DEV(OPT01) VOL(BDS)
RSTLIB(QTEMP) OPTFILE(SPDF40)
```

If you are using a Save file:

```
RSTOBJ OBJ(BOVIN*) SAVLIB(SPDF40) DEV(*SAVF) SAVF(IIII/ffff)
RSTLIB(QTEMP)
```

Enter the lib/name of the save file containing library **SPDF40**.

SPOOL PDF OVERLAY/400™

Press **ENTER**

3) Execute the install procedure. Enter one of the following:

If you are using Tape or CD-ROM:

QTEMP/BOVINS DEV(xxxxx)

If you are using a Save file:

QTEMP/BOVINS DEV(*SAVF) PGMSAVF(aaaaa) DTASAVF(bbbbb)

Enter the save file containing library **SPDF40** for aaaaa. Enter the save file containing library **SPDF40DATA** for bbbbb.

Press **ENTER**.

You will receive the message “Installation of Spool PDF Overlay/400 complete”. You may need to call Broderick Data Systems to activate your 30 day trial package. You will first need to add library **BRODERICK** to your library list.

4) Access the BDS Software Server (optional).

Note: Your AS/400 must be connected to the Internet to perform this procedure.

a) If you have not done so previously, access the tailoring options screen:

BRODERICK/BOVSETUP

b) Note the fields “BDS Access Userid” and “Password”. You will need a user ID and password to access some of the server options. If needed, contact BDS administration to get this information. If you add your user id and password, press **ENTER** to enter them and re-enter the setup command.

c) Press F14, E-Comm. The Software Server display will appear. Take note of the options available to you. When you are finished, press F3 to exit

MAIN MENU

To access Spool PDF Overlay/400 Main Menu, enter the following command:

SPDADM

The following screen should appear:

```
Spool PDF Overlay/400 (TM)      11/30/09  08:58:32
Administrator Main Menu      01 00 0000  QSECOFR

Administration
  1. Tailoring Options          (BOVSETUP)
  2. Manage Option Specifications
  3. Manage Font Global ID (FGID) Table
  4. Manage FGID Substitution Table

Operation
  11. Create a PDF from a Spool File (SPLETOPDF)

  90. Sign off

Selection: _____ F3=Exit  F6=Messages  F10=Command Entry
(C) Copyright 2009, 2010 - Broderick Data Systems
```

Administration

Options 1 thru 4 are used to describe various components to Spool PDF Overlay/400. The above options have the following definitions:

1. Tailoring Options

Allows the Administrator to enter passwords, set various system options, and define Spool PDF Overlay/400 options. For more information, refer to Chapter 4, "Define Tailoring Options".

2. Manage Option Specifications

Allows the definition of Option Specs, which are used by other tasks (i.e. the SPLETOPDF command). They specify options and default values to use when creating a PDF file.

3. Manage Font Global ID (FGID) Table

Allows the definition of FGID Specifications, which contain the PDF attributes needed to create the corresponding font in a PDF file.

4. Manage FGID Substitution Table

Allows the definition of FGIDs to use if the requested FGID is not in the FGID Table described above.

SPOOL PDF OVERLAY/400™

Operation

Option 11 has the following definitions:

11. Create a PDF from a Spool File (SPLETOPDF)

Executes the SPLETOPDF command, which creates a PDF file from the specified spool entry.

DEFINE TAILORING OPTIONS

This allows the Administrator to define system wide options. To access the Tailoring Options screen, select option 1 from the Menu or enter the following command:

BRODERICK/BOVSETUP

The following screen will appear:

```
Spool PDF Overlay/400 (TM)      11/7/09 10:41:07
Setup Display                      Prc
System Statistics: Rel  Mod  PTF  System Name  CPU Serial  Model  Grp
                   01   00   0000  BDS400      00000000   E4A   P05
Passwords: Permanent              Temporary
                   F1F2F3F4F5F6F7F8  FAFBFCFDFF Hex Digits (0-9, A-F)

EBCDIC CCSID:    ___ 37
ASCII CCSID:     ___ 437

BDS Access Userid: _____ Password: _____

F3=Exit w/o Update F12=Exit w/o Update F14=BDS SwSvr
Copyright 2009, 2010 Broderick Data Systems
```

The above parameters have the following definitions:

System Statistics

Rel, Mod and PTF

This is the Release, Modification and Program Temporary Fix level of Spool PDF Overlay/400 you have installed.

Note: When the update to Spool PDF Overlay/400 is done, it will update these fields. If you update Spool PDF Overlay/400 and these fields do not update, verify you have executed the update procedure in the Spool PDF Overlay/400 Update Instructions.

System Name

The system name assigned to the iSeries computer running the Spool PDF Overlay/400 software.

CPU Serial Number

The CPU serial number assigned to this iSeries computer.

SPOOL PDF OVERLAY/400™

Model

The model number of this iSeries computer.

Proc Grp (Processor Group)

The Processor Group of this iSeries computer. The Processor Group is a designation designed by IBM to group its hardware for tiered pricing purposes. BDS also uses IBM's groupings for pricing purposes.

Passwords

Permanent and Temporary Passwords

Passwords are provided by Broderick Data Systems to allow access to Spool PDF Overlay/400. Certain key functions test these passwords before executing. If the password tests fail, a message will appear on the **QSYSOPR** message queue and the function stops.

BDS Access User ID and Password

Specifies the user ID and password needed to access the BDS Software Server. Contact BDS Administration for your user ID and password.

Other Options

EBCDIC and ASCII CCSID

Specifies the EBCDIC to ASCII conversion scheme to use. Please note that the iSeries is an EBCDIC machine and PDF is an ASCII specification. Spool PDF Overlay/400 will convert data from the specified EBCDIC character set ID to the specified ASCII character set ID. For more information refer to AS/400 National Language Support, Appendix G.2 "Code Pages and CCSID's"

Notes:

- 1) Specified CCSID's will be checked by issuing a test string to convert. Errors will be reported back to the user. For a list of errors and their meanings refer to "OS/400 National Language API's", Chapter 3.2.2 "CDRCVRT API Feedback Codes and Conditions". No error message does not insure a proper conversion. We recommend you test the conversion by creating a PDF and displaying it in Adobe Acrobat.
- 2) CCSIDs 37 and 437 are US English EBCDIC and ASCII.

F3 (Return)

Press F3 to exit without updating.

DEFINE TAILORING OPTIONS

Access the BDS Software Server

If **F14** is chosen, the screen showing BDS Software Server options is displayed. To access the BDS Software Server the AS/400 must be connected to the Internet. The following display will appear:

```

12/03/01      11:45:21
BDS Software Server Display

Select one of the following:

1. Check for updates
2. Download Software Update
3. Download Software Patch
4. Upload Captured Problem Data

Option:

F3=Exit  F12=Exit
```

Some of the following options require a user ID and password. If you do not have one, contact BDS Administration. These options use the Internet to connect to a server at Broderick Data Systems. Therefore your AS/400 must be connected to the Internet. If behind a firewall, the firewall must allow outbound sessions through it.

Check for updates

Retrieves the latest available release of the product. Displays the BDS and OS/400 prerequisite releases required to install the latest release of the product.

Download Software Update

Downloads the latest release of the product into save files on your system. The update procedure can then be done using these save files. The product may be active and running while you perform this download.

Download Software Patch

Downloads objects into a save file on your system. Usually you will use this option while working with BDS tech support.

Upload Captured Problem Data

Uploads a save file on your system (containing objects that you have saved) into a save file on the BDS server. Usually you will use this option while working with BDS tech support.

F3 (Return)

SPOOL PDF OVERLAY/400™

Press F3 to exit.

F12 (Return)

Press F12 to exit.

DEFINE OPTION SPECIFICATIONS

Options Specs are used by other tasks to create a PDF. They specify options and default values to use when creating a PDF file.

The default specification, *DFT is shipped with the software. It can be changed by the Administrator but not deleted.

Select F6 to add a new Specification. Enter the name of the Spec to create and press ENTER. The following screen should appear:

```
Spool PDF Overlay/400          ADD          11/06/09
Define Option Specs            10:16:46

Name:  Spec1

Page Method:  *SPLFILE          (*SPLFILE, *TGTSIZE)
Page Length:  11.000
Page Width:   8.500
Unit of Measure: *INCH          (*INCH, *CM)
Rotate Column: 80
Font Global ID: 11
Font Point Size: 12.000
Allow Font Substitution: Y          (Y, N)
Descriptive Text: My Options Spec .

F3=Exit  F12=Cancel Current Operation
```

The above parameters have the following definitions:

Page Method

Specifies, for Device Type *SCS spool entries, the method to use when calculating the page length and width. Specify one of the following:

***SPLFILE:** The attributes retrieved from the spool entry are used to determine the page size.

***TGTSIZE:** The page length and width is determined by the length and width parameters below.

This parameter is ignored for *AFPDS spool entries. The Page Length, Page Width, Unit of Measure, and Rotate Column fields will be ignored if *SPLFILE is used.

Page Length

Specifies, for page method *TGTSIZE, the page length in inches or centimeters (see below). This parameter is ignored for *AFPDS spool entries.

SPOOL PDF OVERLAY/400™

Page Width

Specifies, for page method *TGTSIZE, the page width in inches or centimeters (see below). This parameter is ignored for *AFPDS spool entries.

Unit of Measure

Specifies, for page method *TGTSIZE, the unit of measure to use to calculate the Page Length and Page Width attributes. Select one of the following:

***INCH:** The UOM is inches.

***CM:** The UOM is centimeters.

Page Rotate Column

Specifies, for page method *TGTSIZE, the page minimum page width that will cause the page to be rotated 90 degrees. For example, if 80 is specified and the spool entry's page width is 132 columns, the page will be rotated 90 degrees when the PDF is generated.

Font Global ID

Specifies the default Font Global ID (FGID) to use. Specify a number from 1 to 65535.

The FGID scheme was set up by IBM to uniquely identify a font typestyle and size. The FGID's specified size may be overridden by other attributes. FGID information is contained in various IBM publications. For example, Refer to "Printing V" Appendix D for more information at :

<http://publib.boulder.ibm.com/infocenter/series/v5r3/topic/books/sc415713.pdf>

Font Point Size

Specifies the font's point size. This value may be overridden by other spool entry attributes. Specify zero to set this FGID's point size as unspecified. If unspecified, the point size value will be calculated from CPI and LPP values.

Allow Font Substitution

Specifies the action to take if a font referenced in a spool entry cannot be found, either in the OS/400 library system (i.e. CDEFONT objects) or Spool PDF Overlay/400 specs (i.e. FGID Spec). Specify one of the following:

Y: Another font will be substituted. The Font Substitution Table will be referenced or the Default FGID will be used.

N: No substitution will be attempted. An escape message will be sent to the calling program, causing a function check if not monitored.

Descriptive Text

Specify up to 50 characters of text that describes the Specification.

DEFINE FONT GLOBAL ID (FGID) SPECIFICATIONS

The Define Font Global ID (FGID) Specifications option allows the System Administrator to define Font options used when creating PDF files and email attachments. OS/400 uses a Font Global ID number to describe a font typestyle and point size in spool entries. PDF uses structures called Font Objects to define Fonts. The attributes needed by PDF to convert an FGID into a PDF Font Object are specified here.

Please note that only minor syntax checking is performed. For more information, refer to the Adobe Portable Document Format, PDF Reference by Adobe Systems Incorporated. Refer to Chapter 5.5, "Simple Fonts". Listed below are parameters that have special meanings to Spool PDF Overlay/400.

Std 14

Specifies if this font is one of the Standard 14 fonts defined by the Adobe PDF specification. Standard 14 fonts do not require many of the other attributes to be specified. Specify Y or N.

Point Size

Enter the font's point size. This value may be overridden by other spool entry attributes. Specify zero to set this FGID's point size as unspecified. This is a required field.

Descriptive Text

Specify up to 50 characters of text that describes the Specification.

Optional Fields

Many PDF Font Objects do not always specify all parameters. To specify an optional field, place an X next to it, then fill in the desired value. To deselect a field, place a space next to it.

Note: To enter a negative number, enter the number and press the field-minus key (usually the minus sign (-) on the far right side of the keyboard).

Flags

To enter the Flags attribute, specify Y or N for the appropriate field. The resulting Flags integer will be calculated.

DEFINE FGID SUBSTITUTION TABLE

The Define FGID Substitution Table option allows the System Administrator to define the FGID to use when the desired FGID is not found in the Font Global ID Table. The Administrator can define ranges, or specific FGID from/to values. A specific match takes precedence over a range match.

Select **F6** to add a new entry. Enter The following screen should appear:

```
Spool PDF Overlay/400 (TM)
Add/Copy FGID Specification

FGID Spec to Add/Copy -

Type:  _          (R, S)
From FGID:  _ 0
To FGID:    _ 0

F3=Exit  F12=Cancel Current Operation
```

The above parameters have the following definitions:

Type

Specifies the entry type. Specify one of the following:

R (Range): A range is being specified. The From and To FGIDs will be specified.

S (Specific): A single, specific From FGID will be specified. The To FGID field will be ignored.

From FGID

Specify the Range lower limit (for type R) or From (for type S) FGID.

To FGID

Specify the Range upper limit (for type R) FGID. This parameter will be ignored for type S.

Press **ENTER**. The following screen should appear:

SPOOL PDF OVERLAY/400™

Spool PDF Overlay/400 (TM)	CHANGE	12/22/09
Define FGID Substitution Table		16:43:27
Type: R	From FGID: 1	To FGID: 2
	Substitute FGID: _____	33
F3=Exit F4=Prompt F12=Cancel Current Operation		

The above parameters have the following definitions:

Substitute FGID

Specifies the FGID to substitute. A definition for this FGID must exist in the Font Global ID table.

SPOOL ENTRY TO PDF (SPLETOPDF) COMMAND

The Spool Entry to PDF (SPLETOPDF) command is used to create a PDF from a specified spool entry. The PDF is placed into the specified IFS file. The spool entry can be Device Type *SCS or *AFPDS. Supported Overlays, Fonts, and Images will be preserved.

Enter the **SPLETOPDF** command and press **F4**. The following screens will appear:

```
Spool Entry to PDF (SPLETOPDF)

Type choices, press Enter.

Output PDF Path and File Name . _____
_____

Spool entry's file name . . . . . _____ Name
Spool entry's Job Name . . . . . *CURRENT Name, *CURRENT
  User . . . . . _____ Name
  Number . . . . . _____ 000000-999999
Spool entry's file number . . . *LAST Name, *ONLY, *LAST
Options Spec Name . . . . . *DFT Character value
Data Authorities Assigned . . . *DFT *DFT, *IRUSR, *IWUSR...
      + for more values . *DFT .

F3=Exit  F4=Prompt  F5=Refresh  F12=Cancel  F13=How to use this display
F24=More keys
```

Output PDF Path and File Name (OUTFILE) Parameter

Specifies the IFS path and file name of the file to create. If the file exists it will be unlinked (deleted).

Note: Include a leading forward slash.

Note: File System QDLS is not supported.

Spool entry's file name (SPLFILE) Parameter

Specifies, with the **SPLJOB** and **SPLNBR** parameters, the spool entry to E-Mail. OS/400 uses the combination of Job name, spool file name, and spool file number to uniquely identify a spool entry in the system

Spool entry's Job name (SPLJOB) Parameter

Specifies, with the **SPLFILE** and **SPLNBR** parameters, the spool entry to E-Mail. Specify the Job name, user, and number. The user may also specify one of the following special values:

***CURRENT:** The job that issues the SPLETOPDF command will be used to identify the spool

SPOOL PDF OVERLAY/400™

entry.

Spool entry's file number (SPLNBR) Parameter

Specifies, with the **SPLFILE** and **SPLJOB** parameters, the spool entry to E-Mail. Specify the file number or one of the following special values:

***LAST:** The last spool file that the job created will be sent.

***ONLY:** The only spool file that the job created will be sent.

Options Spec Name (SPECNAME) Parameter

Specifies the Options Spec name to use. The Options Spec name contains parameters used to create the output file, for example Font Size. Use the Manage Option Specifications menu option to create an Options Spec. The possible values are:

***DFT:** The default Options Spec is used.

spec-name: Specify the Options Spec name to use. The spec must have been created using the Manage Option Specifications menu option.

Data Authorities Assigned (DTAAUT) Parameter

Specifies the Data Authorities assigned to the created IFS file. Select one or more of the following:

***DFT:** The *IRWXU and *IRWXO values (see below) will be used.

***IRUSR:** The creating user will have read access to the created file.

***IWUSR:** The creating user will have write access to the created file.

***IXUSR:** The creating user will have execution access to the created file.

***IRWXU:** The creating user will have all access to the created file.

***IRGRP:** The creating user's group will have read access to the created file.

***IWGRP:** The creating user's group will have write access to the created file.

***IXGRP:** The creating user's group will have execution access to the created file.

***IRWXG:** The creating user's group will have all access to the created file.

***IROTH:** The public will have read access to the created file.

***IWOTH:** The public will have write access to the created file.

SPOOL ENTRY TO PDF (SPLETOPDF) COMMAND

***IRWXO:** The public will have all access to the created file.

Example: The following command will take a spool entry (a screen print) created by you and create a PDF. Please note that the Options Spec O1 must be created prior to entering this command:

```
SPLETOPDF OUTFILE('/MyIFSDir/MyPDF.pfg') SPLFILE(QPRINT)  
SPLJOB(*CURRENT) SPLNBR(*LAST) SPECNAME(O1)
```

APPENDIX A: ELECTRONIC MEDIA DISTRIBUTION

The user can distribute Spool PDF Overlay/400 to remote systems electronically. Thus the user can install or update E-mail Utilities on similar remote systems (i.e. AS/400 to AS/400's). A working **APPC/APPN** or **TCP** link to the remote system, and a file transfer program such as **FileXfer3X/400** or **FTP** is needed to do this. Below are the steps you must perform to transmit Spool PDF Overlay/400 to remote systems. **Please note** that a thorough knowledge of the operating systems involved is suggested.

The **AS/400** media consists of **2** libraries:

SPDF40
SPDF40DATA

The steps to distribute Spool PDF Overlay/400 are:

Source System

- 1) Restore libraries **SPDF40** and **SPDF40DATA** from the **BDS**. Media. For optical disk, the libraries are contained in optical files **SPDF40** and **SPDF40D**.

Note: You must be signed on as a user with ***SECADM** authority when performing the restores.

- 2) Create two save files **SAVSPDF** and **SAVSPDFD**.
- 3) Save library **SPDF40** into save file **SAV SPDF**, and library **SPDF40DATA** into save file **SAVSPDFD**.
- 4) Delete the libraries **SPDF40** and **SPDF40DATA**.
- 5) Transmit the save files to the remote system(s).

Remote System(s)

- 1) Create and receive the transmitted save files, if necessary.
- 2) Proceed with the update or install instructions with the following:

When requested to restore the install or update objects into library **QTEMP**, use the save file option. Enter save files **SAVSPDF** and **SAVSPDFD**.

When executing the install or update command (**BOVINS** or **BOVUPD**) use the save file option. Enter save files **SAVSPDF** and **SAVSPDFD**.

Spool PDF Overlay/400 will be installed or updated.

APPENDIX B: RETRIEVE FONT ATTRIBUTES

The Retrieve Font Attributes utility allows the administrator to retrieve a font's attributes from an existing PDF file. The retrieved attributes can be imported into an FGID Spec within the Spool PDF Overlay/400 product. The Retrieve Font Attributes utility program runs on the Microsoft Windows platform.

The Retrieve Font Attributes utility is located in the IFS directory:

/BRODERICK/SPDF40/PGMS/RetrieveFontAttrs

Due to Microsoft DotNet security issues, the administrator should copy this directory to a directory on the PC's hard drive, then execute the program from the hard drive. Once copied, to start the utility execute the file:

RetrieveFontAttrs.exe

Click the Help menu option for detailed help concerning the utility. In general, perform the following steps to import font specifications:

1) **Create a PDF:** Skip this step if the desired font is in an existing PDF file. **Note:** This step requires the PDF driver, which is in Adobe Corp's Acrobat Writer product. Acrobat Writer must be purchased from Adobe Corp.

a) From the Retrieve Font Attributes window, click the Create PDF File button.

b) The "Create a PDF containing a Specific Font" window will appear. Select the following:

- Printer – Must be the Adobe PDF driver
- Font Family
- Style

The em-size is optional; it will not affect the generated font attributes. Click the Go button.

c) The Adobe "Save PDF File As" dialog box will appear. Navigate to the desired folder and type the desired File Name. The Save as Type field should be left as PDF files. Click the Save button. Click yes to replace an existing PDF if asked.

d) The PDF application will open, showing a small 1-page PDF containing the printable ASCII characters. Close the PDF application.

e) Close the Create a PDF window to return to the Retrieve Font Attributes window.

Note: The user can copy/paste the one-page PDF's characters into Microsoft Notepad (or other Windows applications) and print using the PDF driver to achieve the same results as step 1.

2) **Scan the PDF:** Enter the PDF File Name, or Click the Browse button to navigate to and select the desired PDF file. Click the Scan button.

3) **Select the Desired Font:** A list of fonts that were found in the scanned PDF file will appear in the "Fonts in File" listbox. The listbox shows the Object Number within the PDF

SPOOL PDF OVERLAY/400™

file and the Base Font Name. Double-click the desired base font name to select it. Its attributes should appear in the Attributes area.

4) **Save the Attributes:** Enter the Output File Name or click the Browse button to navigate to the desired directory and click the Save button. If possible, navigate to a network directory which points to an iSeries's IFS subdirectory. Click the Export button to create the file.

5) **Copy the file to the iSeries:** IFS: Skip this step if you saved the file to the iSeries IFS in the previous step. Use any method available to copy the file to the iSeries. Do not convert from ASCII to EBCDIC.

6) **Import the Attributes:** The attribute file can be imported into a new or existing FGID spec. For detailed information regarding FGID specs, refer to Chapter 6, "Define FGID Specs". In general, perform the following:

a) Sign on to the iSeries. Enter the following command:

BRODERICK/SPDADM

b) Take option 3, Manage Font Global ID (FGID) Specifications. Press ENTER to show all.

c) Take Option 2 to select the desired FGID spec or press F6 to add and add the new spec. The Define FGID Specs screen should appear.

d) Press F6=Import. The Import FGID Attributes screen will appear. Enter the path and file name created in Step 5. For example:

/MYDIR/Courier.inf

Press ENTER. The attributes are now copied into the FGID spec.

e) Make any desired changes and press ENTER to add/change the FGID spec.

APPENDIX C: ACKNOWLEDGEMENTS

The following third party products have been incorporated into Spool PDF Overlay/400:

Flate - Flate is an industry-standard compress/decompress algorithm written by Jean-loup Gailly and Mark Adler. BDS has adopted their code to run on the AS/400 platform. The Adobe PDF format supports Flate compression. You can contact them at <http://www.gzip.org/>.

LibTiff - LibTiff is an organization that develops tiff-supported compress/decompress algorithms. BDS has adopted their code to run on the AS/400 platform. The CCITT fax decompressions (G3 1D and 2D, and G4) are used. You can contact them <http://www.libtiff.org/>. Per their license agreement:

Copyright (c) 1990-1997 Sam

Copyright (c) 1991-1997 Silicon Graphics, Inc.

Permission to use, copy, modify, distribute, and sell this software and its documentation for any purpose is hereby granted without fee, provided that (i) the above copyright notices and this permission notice appear in all copies of the software and related documentation, and (ii) the names of Sam Leffler and Silicon Graphics may not be used in any advertising or publicity relating to the software without the specific, prior written permission of Sam Leffler and Silicon Graphics