DISPLAY/PURGE THE SENT MAIL LOG

SpoolOrganizer/400 can optionally keep E-Mail in the Sent Mail Log. Users can display sent mail using the **DSPSNTML** command. The command has no parameters. The following screen should appear:

Display Sent E-Mail Display Specifications						
Enter values to limit the search:						
Start Date/Time: <u>1</u>	<u>.9990305</u> 000	0000 End	Date/Time:	999999999	999999	
Sending Job: <u>*</u>	ALL U	Jser: <u>*ALL</u>	Num:	*ALL		
From Address:						
To Address:						
	-					
F3=Exit F12=Cancel	Add/Copy					
(C) Copyright	z 1989, 1999	9 Broderick	Data Syste	ms	

Start/End Date and Time

Specifies the date the mail was sent. Only messages which were sent between the from and to times will be included.

Sending Job

Specifies that attributes from the job which sent the message will be used to search. Only messages which match the specified job name, user profile, or job number will be selected.

From Address

Specifies the from address to search for. Only messages which match the specified from address will be selected.

To Address

Specifies the to address to search for. Only messages which match the specified to address will be selected.

SPOOLORGANIZER/400TM

Press ENTER to search. A screen displaying the results of the search will display:

SpoolOrgar	3/05/99				
1=Disp Attr	2=Chg Att	tr 4=Delete	5=Entries	8=Resend	16:47:00
X SendDate	SendTime	SendJob	SendUser	SndNum	FromName
_ 1999/01/1	.5 10:40:58	GLMONEND	QSYSOPR	025147	System Operator
_ 1999/01/1	11:22:53	APHIST	QUSER	025538	Work Station User
_ 1999/02/2	26 08:50:14	PR02715D	EJONES	419572	Ed Jones
_ 1999/02/2	26 14:15:32	GLMONEND	QSYSOPR	025147	System Operator
F3=Exit E	12=Cancel				
		(C) Copyright	1989, 1999	Broderick	Data Systems

Select from one of the following

1=Display Attr

Displays the attributes used to create the message. See Chapter 31, "Define E-Mail Specifications" for a description of the message's attributes.

2=Chg Attr

Displays the attributes used to create the message and allows the user to change them. See Chapter 31, "Define E-Mail Specifications" for a description of the message's attributes.

4=Delete

Deletes the message from the Sent Mail Log.

5=Entries

Displays the spool entries included in the message. The user can then display the spool entries and their attributes.

8=Resend

Resends the message.

Place a 5 next to an entry to display the spool entries included in the message. The following screen will display:

DISPLAY/PURGE THE SENT MAIL LOG

SpoolOrganizer/400 1=Attr 5=Display			Spool Entries	3/05/99 16:47:00		
x	Job Nam	e Job User	File Name	User Data	Form Type	Pages
	DSP01	QUSER	INV03412	INVPRT	*STD	418
F3	=Exit	F12=Cancel	(C) Copyright	1989, 1999	Broderick Da	ata Systems

Select from one of the following

1=Attr

Displays the attributes of the included spool entry Refer to IBM publications for a description of the spool entry's attributes.

5=Display

Displays the spool entry. See Chapter 29, "Display a Spool Entry" for more information.

Purging Sent Mail

Sent E-mail must be removed from the log using the **PURSNTML** (purge sent mail) command. Entries purged from the sent mail log are gone (they are not moved to a "deleted mail" bin).

```
Purge Sent E-Mail (PURSOLOG)

Type choices, press Enter.

From Date (YYYYMMDD).....

To Date (YYYYMMDD)

99999999

Number

Purge Expired entries only...

*EXPIRED

*ALL, *EXPIRED

F3=Exit F4=Prompt F5=Refresh F12=Cancel F13=How to use this display

F24=More keys
```

The **PURSNTML** command has the following parameters:

From Date (FROMDATE) Parameter

Specifies the date value (message sent date) of the first record to delete.

<u>0</u>: The purge will begin with the first record.

SPOOLORGANIZER/400TM

To Date (TODATE) Parameter

Specifies the date value (message sent date) of the last record to delete.

99999999: The purge will end with the last record.

Note: The mail sent date is stored by SpoolOrganizer in YYYYMMDD format, for example 19990305. Numbers representing valid dates should be specified but this is not a requirement. For example 19990000 can be specified as the From or To date.

Purge expired entries only (TODATE) Parameter

Specifies if the message's expiration date is considered when selecting the date value (message sent date) of the last record to delete.

***EXPIRED:** Only expired messages will be purged. SpoolOrganizer uses the mail sent date and adds the specified retention period to determine the expiration date. The day following the expiration date is the first day the message can be purged. For more information regarding retention periods, see Chapter 31, "Define E-Mail Specifications" section "Period to keep in E-Mail Log".

*ALL: The message's expiration date is not considered when purging messages. All messages which match the other selection criteria will be purged.