DEFINE ARCHIVE/PURGE CRITERIA

Archive or Purge Specifications are used by the following commands. The specifications narrow down the spool entries processed by these commands:

ARCOLE (Archive Spool Entries in the Online Database to Tape)
PUROLE (Purge Entries in the Online Database)
PURARCCAT (Purge the Archive Catalog)
OPTOLE (Archive Spool Entries in the Online Database to Optical)
PUROPTCAT (Purge the Optical Catalog)

For example the user can keep similar spool entries (i.e. Joblogs) archived on the same tape. The following screen will appear:

	SpoolOrganizer 10/12/89					
			Manage Archive or Purge Specifications	8:28:33		
A/O	Field	Rel	Value UC Wild Fiel	ds		
—						
—				b Name		
—				b User		
—				ool File rm ID		
—						
				er Data		
—				er Remark		
				te (1993)		
—				b Number		
				oup Profile		
—			10-Ou	-		
			11-Li	b		
—			12-Pa	ges		
Name to Save or Restore:						
			Text:			
F3=Exit F4=List Saved F9=Save F10=Replace F13=Restore						

A/O: (AND/OR)

Specifies if the test is to be logically ANDed or ORed with the test on the previous line.

Field

SPOOLORGANIZER/400TM

Specifies the spool database attribute to compare for the test. The following attributes and their numbers are valid:

1-Job Name
2-Job User
3-Spool File Name
4-Form ID
5-User Data
6-User Remark
7-Date (YYYYMMDD)
8-Job Number
9-Group Profile of Job User
10-Source Outq Name
11-Source Outq Library
12-Number of Pages

Please Note: Date is the date the job that created the spool entry entered the system.

Rel. (Relation)

Specifies the type of test to perform. The following types are valid:

EQ Equal EQ Not equal GT Greater than NG Not Greater than LT Less than NL Not Less than LE Less than or equal to GE Greater than or equal to CT Contains (The value appears anywhere in the field)

Value

Specifies the value to test for.

* (Job Date only): Substitutes the job date of the workstation job performing the search.

*+nnnnnn (Job Date only): Adds n days to the workstation's job date.

*-nnnnn (Job Date only): Subtracts n days from the workstation's job date.

*USRPRF (Job User only): Substitutes the workstation's User Profile.

UC (Ignore upper/lower case differences)

Specifies if abc is equivalent to ABC, etc. Specify Y to ignore case differences, N to accept case differences. Blank defaults to Y.

DEFINE ARCHIVE/PURGE CRITERIA

Wild (Wild Card Char)

Wild Card Character Specifies if wild characters are present in the value. Wild characters can only be specified if the relation is EQ. Two types of Wild Characters are valid:

*: Matches any number of characters. For example A*C will match AC, AXC, AXXC, etc.

_: Matches any one character. For example A_C will match AXC, ABC etc. but will not match AC, AXXC, etc.

More than one wild character can be specified. For example A*B_C*D_E is valid.

Name to Save or Restore

Specifies the Name to save the specifications under for further reference. The Name will be referred to in the **ARCID** parameter of the **ARCOLE**, **PUROLE**, **PURARCCAT**, **OPTOLE** and **PUROPTCAT** commands.

Text

Specify up to 30 characters of descriptive text.

Example: To keep all archived joblogs on the same tape, perform the following:

1) Enter the following on the screen shown above:

<u>Field</u>	<u>Rel</u>	<u>Value</u>
3 (Splf name)	EQ	QPJOBLOG

- 2) Save the specifications. The name to save is your choice. For example use **JOBLOGS**. Enter "Archive Job Logs" in the text field. Press **F9** to save.
- 3) Enter the archive Online Database spool entries command:

ARCOLE ARCID(JOBLOGS) DEV(xxxxx)

The joblogs will be archived.